

SAFETY DATA SHEET

1. Identification

Product identifier WELD-KLEEN® HD® - 1 lb 4 oz

Other means of identification

No. 007030 (Item# 1008284) **Product Code**

Recommended use Protects parts, fixtures, and tooling from spatter build-up

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section Recommended restrictions

3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

General Information 215-674-4300 **Technical Assistance** 800-521-3168 **Customer Service** 800-272-4620 24-Hour Emergency

(CHEMTREC)

800-424-9300 (US)

Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Gases under pressure Compressed gas

Health hazards Acute toxicity, oral Category 4

> Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2A Carcinogenicity Category 1B

Specific target organ toxicity, single exposure Category 3 narcotic effects

Specific target organ toxicity, repeated Category 2

exposure

Environmental hazards Not classified. Not classified. **OSHA** defined hazards

Label elements



Signal word Danger

Contains gas under pressure; may explode if heated. Harmful if swallowed. Causes skin irritation. **Hazard statement**

Causes serious eye irritation. May cause drowsiness or dizziness. May cause cancer. May cause

damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 49 °C/120 °F. Do not breathe mist or vapor. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

Material name: WELD-KLEEN® HD® - 1 lb 4 oz SDS US

If swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth. If on skin: Wash with Response

plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If exposed or concerned: Get medical

advice/attention.

Store locked up. Protect from sunlight. Store in a well-ventilated place. Exposure to high Storage

temperature may cause can to burst.

Disposal Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal

corrosive gases such as hydrogen chloride and possibly phosgene.

3. Composition/information on ingredients

Mixtures

Ingestion

Chemical name	Common name and synonyms	CAS number	%
methylene chloride		75-09-2	80 - 90
carbon dioxide		124-38-9	5 - 10
high oleic safflower oil		8001-23-8	5 - 10

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get

medical advice/attention. Wash contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May

Get medical advice/attention if you feel unwell.

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Most important

symptoms/effects, acute and delayed

Indication of immediate

medical attention and special treatment needed

General information

cause redness and pain. Prolonged exposure may cause chronic effects. Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from

the chemical

Do not use water jet as an extinguisher, as this will spread the fire. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

health may be formed. When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal corrosive gases such as hydrogen chloride and possibly phosgene.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment/instructions General fire hazards

In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.

Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

Material name: WELD-KLEEN® HD® - 1 lb 4 oz

SDS US No. 007030 (Item# 1008284) Version #: 01 Issue date: 06-26-2019

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Do not breathe mist or vapor. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Contents under pressure. Do not expose to heat or store at temperatures above 120 °F/49 °C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

Value

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Components

Type

- · · · · · · · · · · · · · · · · · · ·			
methylene chloride (CAS 75-09-2)	STEL	125 ppm	
	TWA	25 ppm	
US. OSHA Table Z-1 Limits for Air Con	taminants (29 CFR 1910.1000)		
Components	Туре	Value	Form
carbon dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
		5000 ppm	
high oleic safflower oil (CAS 8001-23-8)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
US. ACGIH Threshold Limit Values			
Components	Туре	Value	
carbon dioxide (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	

Material name: WELD-KLEEN® HD® - 1 lb 4 oz

US. ACGIH Threshold Limit Values Components	s Type	Value	
methylene chloride (CAS 75-09-2)	TWA	50 ppm	
US. NIOSH: Pocket Guide to Chem	nical Hazards		
Components	Туре	Value	Form
carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	
high oleic safflower oil (CAS 8001-23-8)	TWA	5 mg/m3	Respirable mist.
		10 mg/m3	Total mist

Biological limit values

ACGIH Biological	Exposure Indices
Components	Value

Components	Value	Determinant	Specimen	Sampling Time
methylene chloride (CAS 75-09-2)	0.3 mg/l	Dichlorometha ne	Urine	*

^{* -} For sampling details, please see the source document.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Wear protective gloves such as: Polyvinyl alcohol (PVA). Viton/butyl. Hand protection

Other Wear appropriate chemical resistant clothing.

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a Respiratory protection

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. Aerosol. **Form** Colorless. Color Ether-like. Odor **Odor threshold** Not available. pН Not available.

Melting point/freezing point -139 °F (-95 °C) estimated Initial boiling point and boiling 104 °F (40 °C) estimated range

Flash point

None. **Evaporation rate** Fast.

Not available. Flammability (solid, gas)

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

15.5 % estimated

Flammability limit - upper

(%)

66.4 % estimated

3890.8 hPa estimated Vapor pressure

> 1 (air = 1)Vapor density Relative density 1.31 estimated

Solubility(ies)

Solubility (water) Negligible. Partition coefficient Not available.

(n-octanol/water)

1033 °F (556.1 °C) estimated **Auto-ignition temperature**

Decomposition temperature Not available. Not available. Viscosity Percent volatile 87.5 % estimated

Other information

0.07 **VOC-State Aerosol**

Coatings (MIR)

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. **Chemical stability**

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Heat, flames and sparks. When exposed to extreme heat or hot surfaces, vapors may decompose

to harmful or fatal corrosive gases such as hydrogen chloride and possibly phosgene. Contact with

incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Carbon oxides. Hydrogen chloride. Phosgene.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause damage to organs through prolonged or repeated exposure by inhalation. May cause

drowsiness and dizziness. Headache. Nausea, vomiting.

Causes skin irritation. Skin contact

Causes serious eye irritation. Eye contact

Harmful if swallowed. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May

cause redness and pain.

Information on toxicological effects

Harmful if swallowed. **Acute toxicity**

Components **Species Test Results**

methylene chloride (CAS 75-09-2)

Acute Dermal

LD50 Rabbit > 2000 mg/kg

Inhalation

LC50 Rat 52 mg/l, 6 Hours

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye Causes serious eve irritation.

No. 007030 (Item# 1008284) Version #: 01 Issue date: 06-26-2019

irritation

Material name: WELD-KLEEN® HD® - 1 lb 4 oz

SDS US

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

methylene chloride (CAS 75-09-2) 2A Probably carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052) methylene chloride (CAS 75-09-2) Cancer

US. National Toxicology Program (NTP) Report on Carcinogens

methylene chloride (CAS 75-09-2)

Reasonably Anticipated to be a Human Carcinogen.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may

be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

methylene chloride (CAS 75-09-2)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) 1250 mg/l, 48 hours

Fish LC50 Fathead minnow (Pimephales promelas) 140.8 - 277.8 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

methylene chloride 1.25

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsThis material and its container must be disposed of as hazardous waste. Collect and reclaim or

dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not

puncture, incinerate or crush. Dispose in accordance with all applicable regulations.

Hazardous waste code F002: Waste methylene chloride - Spent halogenated solvent

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, poison, Limited Quantity

Transport hazard class(es)

Class 2.2
Subsidiary risk 6.1(PGIII)
Label(s) 2.2, 6.1
Packing group Not applicable.

Special precautions for user Forbidden from transportation by air.

Material name: WELD-KLEEN® HD® - 1 lb 4 oz

No. 007030 (Item# 1008284) Version #: 01 Issue date: 06-26-2019 6 /

Packaging exceptions306Packaging non bulkNonePackaging bulkNone

IATA

UN number UN1950

UN proper shipping name Transport hazard class(es) Aerosols, non-flammable, containing substances in Division 6.1, Packing Group III

Class 2.2 Subsidiary risk 6.1

Packing group Not applicable.

ERG Code 2P

Special precautions for user Not available.

Other information

Passenger and cargo

Allowed with restrictions.

aircraft

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1950 UN proper shipping name AEROSOLS

Transport hazard class(es)

Class 2.2 Subsidiary risk 6.1


Packing group Not applicable.

Environmental hazards


Marine pollutant No.

EmS Not available. Special precautions for user Not available.

DOT



IATA; IMDG



15. Regulatory information

US federal regulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

methylene chloride (CAS 75-09-2)

0.1 % Annual Export Notification required.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

methylene chloride (CAS 75-09-2) Cancer

Heart

Central nervous system

Liver Skin irritation Eye irritation

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

methylene chloride (CAS 75-09-2)

CERCLA Hazardous Substance List (40 CFR 302.4)

methylene chloride (CAS 75-09-2)

CERCLA Hazardous Substances: Reportable quantity

methylene chloride (CAS 75-09-2)

1000 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

methylene chloride (CAS 75-09-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

Food and Drug Administration (FDA) Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard Gas under pressure

Acute toxicity (any route of exposure) categories

Skin corrosion or irritation

Serious eye damage or eye irritation

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
methylene chloride	75-09-2	80 - 90	

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

carbon dioxide (CAS 124-38-9) methylene chloride (CAS 75-09-2)

US. Massachusetts RTK - Substance List

carbon dioxide (CAS 124-38-9)

high oleic safflower oil (CAS 8001-23-8)

methylene chloride (CAS 75-09-2)

US. Pennsylvania Worker and Community Right-to-Know Law

carbon dioxide (CAS 124-38-9)

high oleic safflower oil (CAS 8001-23-8)

methylene chloride (CAS 75-09-2)

US. Rhode Island RTK

carbon dioxide (CAS 124-38-9)

high oleic safflower oil (CAS 8001-23-8)

No. 007030 (Item# 1008284) Version #: 01 Issue date: 06-26-2019

methylene chloride (CAS 75-09-2)

California Proposition 65



WARNING: Cancer - www.P65Warnings.ca.gov

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Inventory name

methylene chloride (CAS 75-09-2) Listed: April 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

methylene chloride (CAS 75-09-2)

Volatile organic compounds (VOC) regulations

VOC content (40 CFR 0 %

51.100(s))

State

Maximum incremental 0.07

reactivity (MIR)

Other VOC regulations

This product is not compliant to be sold for use in California. This product is compliant in all other states.

International Inventories

Country(s) or region

Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

Issue date 06-26-2019 **Dustin Kern** Prepared by

Version # 01

Disclaimer The information contained in this document applies to this specific material as supplied. It may not

> be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries, Inc..

Revision information Hazard(s) identification: Response

Transport Information: Material Transportation Information

Material name: WELD-KLEEN® HD® - 1 lb 4 oz

No. 007030 (Item# 1008284) Version #: 01 Issue date: 06-26-2019

On inventory (yes/no)*

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).