

MATERIAL SAFETY DATA SHEET**Warren Unilube, Inc.**

Address: 915 E. Jefferson Ave.
West Memphis, AR 72301

Phone: (800) 428-9284

Chemtree Number:
Domestic: 800-424-9300
International: 703-527-3887

PRODUCT IDENTIFICATION

Trade Name: Coastal Premium GL-5 75w90, 80w90, 85w140
Outboard Gear Lube 80w90

Date Revised: September 8, 2006

Synonyms/Product Code: N.A.
Chemical Name: Petroleum Mineral Oil
Family Description: A complex combination of hydrocarbons from a petroleum fraction obtained by solvent crystallization plus additives.
Shipping Information: DOT Hazard Class-Not Applicable.

NEPA Codes: Health=0, Flammability=1, Reactivity=0

COMPOSITION

<u>Product</u>	<u>CAS Number</u>	<u>Wt%</u>	<u>Occupational Exposure Limits*</u>			<u>Units</u>
			<u>OSHA</u> <u>PEL</u>	<u>ACGIH</u> <u>TLV</u>	<u>Other</u>	
Coastal Premium GL-5 75w90, 80w90, 85w140 Outboard Gear Lube 80w90	Mixture	100	N.A.	N.A.	N.A.	N.A.
<u>Ingredient(s):</u>						
Solvent Dewaxed Heavy Paraffinic Petroleum Distillate	64742-65-0	>85	5	5	10 STEL	mg/m ³ †
Solvent Refined Residual Oil	64742-62-7	7	5	5	10 STEL	mg/m ³ **
Additives containing polymers	N.A.	5-8	N.A.	N.A.	N.A.	N.A.

* = 8-Hr. TWA unless otherwise specified.

** = As mineral oil mist

N.A. = Not Available

STEL = Short Term Exposure Limit; 15 minutes.

PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point 760 mmHg:	N.A.	Melting Point:	N.A.
Vapor Pressure mmHg @ 100F:	N.A.	Vapor Density (air=1):	N.A.
Solubility in H ₂ O %:	Nil	pH:	N.A.
Specific Gravity (H ₂ O):	0.9013	Evaporation Rate:	
% Volatile by Volume:	N.A.	(ethyl ether=1):	N.A.
Viscosity (method,temp):	14 cSt @100C	Odor:	Slight hydrocarbon odor
Appearance:	Light amber liquid		

N.A. = Not Available

FIRE AND EXPLOSION DATA

Flash Point:	500°F	
Flammable Limits in Air % by Vol:	Lower: N.A.	Upper: N.A.
Autoignition Temperature:	N.A.	
Extinguishing Media:	Dry chemical, foam, carbon dioxide, or water spray.	
Special Fire Fighting Procedure:	Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool. Firefighters should wear self-contained breathing apparatus.	
Unusual Fire or Explosion Hazard:	May ignite when sufficient heat is applied.	

REACTIVITY DATA

Stability:	Stable
Hazardous Polymerization:	Will not occur.
Conditions to Avoid/Incompatibility:	Strong oxidizing agents, heat, spark, flame and build-up of static electricity.
Hazardous Decomposition Products:	Hydrogen sulfide, carbon monoxide, carbon dioxide, aldehydes, ketones, and combustion products of sulfur and nitrogen.

HEALTH HAZARD DATA

This product has not been tested as a whole to determine its specific health hazards. The information provided in this section is based on health hazard information on the product components.

Carcinogenicity: NTP: No	IARC Monographs: No	OSHA Regulated: No
Occupational Exposure Limits:	See <u>COMPOSITION</u> section.	

Effects of Overexposure:**Acute:**

Eyes: Mildly irritating to the eyes. Injury to the eye may occur if product is not removed promptly.

Skin: May cause slight skin irritation.

Inhalation: The inhalation hazards of the components are negligible to minimally irritating if airborne concentrations are kept below permissible occupational exposure limits. Inhalation of oil mist or vapors at elevated temperatures may cause respiratory irritation, drowsiness, dizziness, headache and nausea.

Ingestion:	Ingestion of large amounts may cause headache, drowsiness, nausea, vomiting or diarrhea. Aspiration hazard if vomiting occurs.
<u>Chronic:</u>	Frequent or prolonged contact may cause skin irritation. Repeated excessive exposure to mists may cause pulmonary irritation or chronic bronchitis.
Additional Medical and Toxicological Information:	May aggravate pre-existing dermatitis. The International Agency for Research on Cancer (IARC) has determined that there is sufficient evidence for the carcinogenicity of used oils in experimental animals.

EMERGENCY FIRST AID PROCEDURES

Eye Contact:	Flush thoroughly with water for at least 15 minutes, including under the eyelids. Contact a physician immediately, preferably an Ophthalmologist. Speed and thoroughness in rinsing eyes are important to avoid permanent injury.
Skin Contact:	Remove contaminated clothing. Wash affected areas with soap and water. If irritation occurs, get medical attention.
Inhalation:	Remove to fresh air. If breathing has stopped, apply artificial respiration. Get immediate medical attention.
Ingestion:	Do not induce vomiting. If spontaneous vomiting occurs hold the victim's head lower than hips to prevent aspiration.

SPECIAL PROTECTION INFORMATION

Eye Protection:	Remove contact lenses and wear chemical safety goggles where contact with liquid or mist may occur.
Skin Protection:	Wear impervious gloves when contact with skin may occur. Use face shield where splashing may occur. Wash with soap and water before eating, drinking or smoking. Launder contaminated clothing before reuse.
Inhalation:	Use Approved respiratory protective equipment for cleaning large spills or entry into large tanks, vessels or other confined spaces or in situations where exposure may exceed occupational exposure levels.
Ventilation:	Provide adequate general and local exhaust ventilation: (1) to keep mist or vapors below occupational exposure levels; and (2) to prevent the formation of an oxygen deficient atmosphere, particularly in a confined space area.

SPILL OR LEAK AND DISPOSAL PROCEDURES

Spill Procedures:	Remove sources of heat or ignition including internal combustion engines and power tools. Remove spill with vacuum trucks or pump and soak up residue with an absorbent. Use approved respirator where occupational exposure limits may be exceeded.
Waste Disposal:	Dispose of through a licensed waste disposal company. Follow federal, state and local regulations.