

SAFETY DATA SHEET

Issuing Date 14-Dec-2016 **Revision Date** Revision Number 0 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING 1. **GHS Product Identifier** Product Name: **TruFlex Rubberized Crack Sealant** Other Means of Identification Product Code(s): M1008 Synonyms None Recommended Use of the Chemical and Restrictions on Use Recommended Use: No Information Available Uses Advised Against: No Information Available Manufacturer's Details Manufacturer Address ThorWorks Industries, Inc. 2520 S. Campbell St. Sandusky, OH 44870 www.sealmaster.net 1-800-326-1994 **Emergency Telephone Number** Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

This product is not considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200).

GHS Label Elements, Including Precautionary Statements

		Emergency Overview	
	Warning nful if swallowed cause skin irritation		
Appearance: Black		Physical State: Mastic	Odor: Asphaltic
Precautionary Statements			
Prevention	Inhalation: Eye Contact: Skin Contact: Ingestion:	May cause irritation of respiratory tract. Contact with eyes may cause irritation. May cause irritation. Ingestion may cause stomach discomfort.	
General Advice Storage Disposal	NoneKeep container tight	č	egional, or local
Hazard Not Otherwise Clas Not applicable	ssified (HNOC)		

3. COMPOSITION/INFORMATION ON INGREDIENTS

	5. COMPOSITION/IN		
Chemical Name	CAS Number	Weight %	Trade Secret
Asphalt	8052-42-4	35-55	*
Attapulgite	12174-11-7	0-10	*
Kaolin	1332-58-7	10-20	*
Polymer	Proprietary	10-40	*
*The exact percentage of composit	ion has been withheld as a trac	de secret.	
	4. FIRS	T AID MEASURES	
Description of Necessary First-A			
Eye Contact	physician.	enty of water, also under the eye	elids. If symptoms persist, call a
Skin Contact		h soap and plenty of water. In	the case of skin irritation or allergic
	Wash off immediately with soap and plenty of water. In the case of skin irritation or allergic reactions, see a physician.		
Inhalation		ptoms persist, call a physician.	
Ingestion		NOT induce vomiting. Never	give anything by mouth to an
	unconscious person. Co	nsult a physician if necessary.	
Most Important Symptoms/Effect	ts. Acute and Delaved		
Most Important Symptoms/Effect			
Indication of Immediate Medical			
Notes to Physician	Treat Symptomatically.	May cause sensitization by skin	contact.
	5. FIRE-FI	GHTING MEASURES	
Suitable Extinguishing Media			
Carbon Dioxide (CO ₂). Dry Chemic	al. Foam. Water Fog.		
Unsuitable Extinguishing Med	lia CAUTION: Use of water si	orav when fighting fire may be i	nefficient.
Specific Hazards Arising from the	<u>e Chemical</u>		
No information available			
Explosion Data			
Sensitivity to Mechanical Impa	act None	9	
Sensitivity to Static Discharge			
Protective Equipment and Preca			
As in any fire, wear self-contained to gear.	preatning apparatus pressure-	demand MSHA/NIOSH (approv	ed or equivalent) and full protective
	6. ACCIDENTA	AL RELEASE MEASURES	
Developed Dressutions Dretestive	Equipment and Emergency	Dragaduraa	
Personal Precautions, Protective Personal Precautions:	Equipment, and Emergency	tion. Avoid contact with skin, ev	es and clothing. Use personal
rersonal recautions.	protective equipment.		tes and clothing. Ose personal
	Letter adarbination		
Environmental Precautions			
Environmental Precautions:	See Section 12 for addition	onal Ecological Information	
Mathada and Matariala fan Canta	in mont and Cleaning Un		
Methods and Materials for Conta Methods for Containment:	Inment and Cleaning Up Prevent further leakage (or spillage if safe to do so.	
		n spillage il sale lo uo so.	
Mothods for Cloaning Lin			and transfer to properly labeled
Methods for Cleaning Up:		ert absorbent material. Pick up	and transfer to properly labeled
Methods for Cleaning Up:			and transfer to properly labeled
	containers. Clean contar	ert absorbent material. Pick up	and transfer to properly labeled
	containers. Clean contar	ert absorbent material. Pick up minated surface thoroughly.	o and transfer to properly labeled
Precautions for Safe Handling	containers. Clean contar 7. HANDL	ert absorbent material. Pick up minated surface thoroughly.	
	containers. Clean contar 7. HANDL Handle in accordance wit	ert absorbent material. Pick up minated surface thoroughly. ING AND STORAGE th good industrial hygiene and s	safety practice. Avoid contact with
Precautions for Safe Handling	containers. Clean contar 7. HANDL Handle in accordance wit skin, eyes, and clothing.	ert absorbent material. Pick up minated surface thoroughly. ING AND STORAGE th good industrial hygiene and s Wear personal protective equip	safety practice. Avoid contact with oment. Avoid breathing vapors or
Precautions for Safe Handling	Containers. Clean contar 7. HANDL Handle in accordance wit skin, eyes, and clothing. mists. Do not eat, drink,	ert absorbent material. Pick up minated surface thoroughly. ING AND STORAGE th good industrial hygiene and s	safety practice. Avoid contact with oment. Avoid breathing vapors or
Precautions for Safe Handling	containers. Clean contar 7. HANDL Handle in accordance wit skin, eyes, and clothing.	ert absorbent material. Pick up minated surface thoroughly. ING AND STORAGE th good industrial hygiene and s Wear personal protective equip	safety practice. Avoid contact with oment. Avoid breathing vapors or
Precautions for Safe Handling	Containers. Clean contar 7. HANDL Handle in accordance wit skin, eyes, and clothing. mists. Do not eat, drink, handling. uding Any Incompatibilities	ert absorbent material. Pick up minated surface thoroughly. ING AND STORAGE th good industrial hygiene and s Wear personal protective equip or smoke when using this produ	safety practice. Avoid contact with oment. Avoid breathing vapors or
Precautions for Safe Handling Handling: Conditions for Safe Storage, Incl Storage:	containers. Clean contar 7. HANDL Handle in accordance wit skin, eyes, and clothing. mists. Do not eat, drink, handling. uding Any Incompatibilities Keep container tightly clo	ert absorbent material. Pick up minated surface thoroughly. ING AND STORAGE th good industrial hygiene and s Wear personal protective equip or smoke when using this produced posed	safety practice. Avoid contact with oment. Avoid breathing vapors or
Precautions for Safe Handling Handling: Conditions for Safe Storage, Incl	Containers. Clean contar 7. HANDL Handle in accordance wit skin, eyes, and clothing. mists. Do not eat, drink, handling. uding Any Incompatibilities	ert absorbent material. Pick up minated surface thoroughly. ING AND STORAGE th good industrial hygiene and s Wear personal protective equip or smoke when using this produced posed	safety practice. Avoid contact with oment. Avoid breathing vapors or

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Asphalt 8052-42-4	TWA: 0.5 mg/m ³ benzene soluble aerosol fume, inhalable fraction	-	Ceiling: 5 mg/m³ fume 15 min.
Kaolin 1332-58-7	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA 5 mg/m ³ respirable fraction	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable dust
Attapulgite 12174-11-7	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA 5 mg/m ³ respirable fraction	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable dust
Appropriate Engineering Co Engineering Measures:	n <u>trols</u> Showers Eyewash Stations		

Eyewash Stations Ventilation Systems

Individual Protection Measures, such as Personal Protective Equipment

Eye/Face Protection: Skin and Body Protection: Respiratory Protection:	If splashes are likely to occur, wear: Safety glasses with side shields. Impervious gloves. No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.
Hygiene Measures:	Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State: Odor:	Liquid Asphaltic		Appearance Odor Three	Black No Information Available
Property pH Melting Point/Rang Boiling Point/Boilin Flash Point Evaporation Rate Flammability (solid Flammability (solid Flammability (solid Flammability (solid Flammability (solid Vapor Pressure Vapor Density Specific Density Water Solubility Solubility in other s Partition coefficien Autoignition Temp Decomposition Temp Viscosity Flammable Properti	le ng Range l, gas) s in Air lity limit lity limit solvents t: n-octanol/water erature nperature ties es	No data available No data available No data available Not Flammable No data available		/Method wm wm wm wm wm wm wm wm wm wm wm wm wm
Oxidizing Propertie VOC Content	70	No data available Less than 15 g/L		

10. STABILITY AND REACTIVITY

Reactivity: Chemical Stability: Possibility of Hazardous Reactions: Hazardous Polymerization: Conditions to Avoid:	Hazardous polymerization does not occur. None known
Incompatible Materials:	None known Strong oxidizing agents. Acids. Carbon Monoxide (CO), Carbon Dioxide (CO ²), Hydrogen Sulfide, Nitrogen Dioxide

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Product Information

Inhalation: Eye Contact: Skin Contact: Ingestion: May cause irritation of respiratory tract. Contact with eyes may cause irritation. May cause irritation. Ingestion may cause stomach discomfort.

Chemical Name	LD50 Oral	LD50 Dermal	LD50 Inhalation
Asphalt	5000 mg/kg (Rat)	>2000 mg/kg (Rabbit)	-

Symptoms Related to the Physical, Chemical, and Toxicological Characteristics Symptoms: No information available.

Delayed and Immediate Effects and also Chronic Effects from Short and Long Term Exposure

Sensitization: Mutagenic Effects: Carcinogenicity:

No information available. No information available.

The table below indicates whether each agency has listed any ingredient as a carcinogen. The IARC, NTP, and OSHA do not list asphalt as a carcinogen. In general, the oxidation of polycyclic aromatic hydrocarbons destroys their carcinogenic potential. Petroleum asphalt, shale oil asphalts, and coal tars show distinct variation in their relative carcinogenicity for experimental animals.

Chemical Name	ACGIH	IARC	NTP	OSHA
Asphalt	A3	Group 2B	Reasonably Anticipated	х

ACGIH: (American Conference of Governmental Industrial Hygienists) A3 – Animal Carcinogen IRAC: (International Agency for Research on Cancer) Group 2B – Possibly Carcinogenic to Humans NTP: (National Toxicity Program) Reasonably Anticipated – Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

X – Present

Reproductive Toxicity:	No information available.
STOT - Single Exposure:	No information available.
STOT – Repeated Exposure:	No information available.
Aspiration Hazard:	No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Persistence and Degradability:	No information available.
Bioaccumulation	

Chemical Name	Log Pow
Asphalt	6006

Other Adverse Effects:

No information available.

	13. DISPOSAL CONSIDERATIONS
Waste Disposal Methods:	This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.
Contaminated Packaging:	Do not re-use empty containers.
	14. TRANSPORTATION INFORMATION
DOT:	Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA – Complies DSL/NDSL – Complies

Legend

TSCA – United States Toxic Substances Control Act Section 8(b) Inventory **DSL/NDSL** – Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS Number	Weight %	SARA 313 – Threshold Values %
Asphalt	8052-42-4	20-40	0.1

SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific requirements at the local, regional, or state level pertaining to releases of this material.

<u>U.S. State Regulations</u> California Proposition 65:

ia Proposition 65: This produ

This product does not contain any Proposition 65 chemicals.

U.S. State Right-To-Know Regulations

"X" designates that the ingredients are listed on the state right to know list.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Asphalt	Х	Х	Х		Х
Kaolin	Х	Х	Х		Х

U.S. EPA Label Information

EPA Pesticide Registration Number:

Not applicable

16. OTHER INFORMATION							
<u>NFPA</u>	Health Hazard: 1	Flammability: 0	Instability: 0	Physical and Chemical Hazards-			
<u>HMIS</u>	Health Hazard: 1	Flammability: 0	Physical Hazard: 0	Personal Protection: X			
Revision Date: Revision Note:	14-Dec-2016 No information	available					

<u>General Disclaimer</u> The information provided on this SDS is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.