



# MULTIMAX™ Lite

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Revision Date: 10/01/2019

Supersedes Date: 10/08/2018

Date of Issue: 05/24/2018

Version: 3.0

## SECTION 1: IDENTIFICATION

### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** MULTIMAX™ Lite

### 1.2. Intended Use of the Product

Adhesive. For professional use only.

### 1.3. Name, Address, and Telephone of the Responsible Party

#### Company

LATICRETE International

1 Laticrete Park, N

Bethany, CT 06524

T (203)-393-0010

[www.laticrete.com](http://www.laticrete.com)

#### Company

LATICRETE Canada ULC

PO Box 129, Emeryville, Ontario, Canada

NOR-1A0

### 1.4. Emergency Telephone Number

**Emergency Number** : For chemical emergency call ChemTel day or night:

(800)255-3924 (North America)

(800)-099-0731 (Mexico)

+1 (813)248-0585 (International - collect calls accepted)

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the Substance or Mixture

#### GHS-US/CA Classification

Skin Corr. 1C H314

Eye Dam. 1 H318

Skin Sens. 1 H317

Carc. 1A H350

STOT SE 3 H335

Aquatic Acute 3 H402

Full text of hazard classes and H-statements : see section 16

### 2.2. Label Elements

#### GHS-US/CA Labeling

##### Hazard Pictograms (GHS-US/CA)



##### Signal Word (GHS-US/CA)

: Danger

##### Hazard Statements (GHS-US/CA)

: H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H335 - May cause respiratory irritation.

H350 - May cause cancer (Inhalation).

H402 - Harmful to aquatic life.

##### Precautionary Statements (GHS-US/CA)

: P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe dust, fume.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves, protective clothing, and eye protection.

# MULTIMAX™ Lite

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P310 - Immediately call a POISON CENTER or doctor.  
P321 - Specific treatment (see section 4 on this SDS).  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P405 - Store locked up.  
P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

### 2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

### 2.4. Unknown Acute Toxicity (GHS-US/CA)

No data available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product Identifier	% *	GHS Ingredient Classification
Cement, portland, chemicals	(CAS-No.) 65997-15-1	75.4-78.1	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335
Calcium oxide	(CAS-No.) 1305-78-8	41.5-54.7	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 3, H402
Copolymer of vinyl acetate and ethylene with mineral additives and protective colloid	(CAS-No.) Not available	7-13	Comb. Dust
Perlite	(CAS-No.) 93763-70-3	7-13	Not classified
Limestone	(CAS-No.) 1317-65-3	3.8 - 3.9	Not classified
Calcium Sulfate Hemihydrate	(CAS-No.) 13397-24-5	3.8 - 3.9	Not classified
Magnesium oxide (MgO)	(CAS-No.) 1309-48-4	2.26 - 2.34	Not classified
Calcium formate	(CAS-No.) 544-17-2	0.1 - 2	Eye Dam. 1, H318
Quartz	(CAS-No.) 14808-60-7	0.75 – 0.78	Carc. 1A, H350 STOT SE 3, H335 STOT RE 1, H372
Chromium, ion (Cr6+)	(CAS-No.) 18540-29-9	0.00007 – 0.00008	Skin Sens. 1, H317 Carc. 1B, H350 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-phrases: see section 16

\* Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

\*\* The actual concentration of ingredient(s) is withheld as a trade secret in accordance with the Hazardous Products Regulations (HPR) SOR/2015-17 and 29 CFR 1910.1200.

# MULTIMAX™ Lite

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### SECTION 4: FIRST AID MEASURES

#### 4.1. Description of First-aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** Using proper respiratory protection, move the exposed person to fresh air at once. Encourage exposed person to cough, spit out, and blow nose to remove dust. Immediately call a poison center, physician, or emergency medical service.

**Skin Contact:** Immediately remove contaminated clothing. Immediately flush skin with plenty of water for at least 30 minutes. Get immediate medical advice/attention.

**Eye Contact:** Immediately rinse with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

#### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**General:** Causes severe skin burns and eye damage. May cause respiratory irritation. May cause cancer (Inhalation).

**Inhalation:** May be corrosive to the respiratory tract. Accelerated Silicosis can occur with exposure to high concentrations of respirable crystalline silica over a relatively short period; lung lesions can appear within five years of the initial exposure. The progression can be rapid. Accelerated silicosis is similar to chronic or ordinary silicosis, except that lung lesions appear earlier and the progression is more rapid.

Acute Silicosis can occur with exposures to very high concentrations of respirable crystalline silica over a very short time period, sometimes as short as a few months. The symptoms of acute silicosis include progressive shortness of breath, fever, cough and weight loss. Acute silicosis can be fatal.

**Skin Contact:** May cause an allergic skin reaction. Redness, pain, swelling, itching, burning, dryness, and dermatitis. Concrete may cause dry skin, discomfort, irritation, severe burns, and dermatitis. Unhardened concrete is capable of causing dermatitis by irritation and allergy. Concrete dust, in association with sweat and friction, can lead to skin irritation and dermatitis. Skin affected by dermatitis may include symptoms such as, redness, itching, rash, scaling, and cracking. Allergic contact dermatitis is caused by sensitization to hexavalent chromium (chromate) present in concrete. The reaction can range from a mild rash to severe skin ulcers.

**Eye Contact:** Causes permanent damage to the cornea, iris, or conjunctiva. Concrete may cause immediate or delayed irritation or inflammation. Eye contact with wet concrete can cause moderate eye irritation, chemical burns and blindness. Eye exposures require immediate first aid and medical attention to prevent significant damage to the eye.

**Ingestion:** May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

**Chronic Symptoms:** Causes damage to organs through prolonged or repeated exposure. May cause cancer. Repeated exposure to respirable (airborne) crystalline silica dust will cause lung damage in the form of silicosis. Some studies show that exposure to respirable crystalline silica (without silicosis) or that the disease silicosis may be associated with the increased incidence of several autoimmune disorders such as scleroderma (thickening of the skin), systemic lupus erythematosus, rheumatoid arthritis and diseases affecting the kidneys. Silicosis increases the risk of tuberculosis. Some studies show an increased incidence of chronic kidney disease and end-stage renal disease in workers exposed to respirable crystalline silica.

#### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

### SECTION 5: FIRE-FIGHTING MEASURES

#### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Use extinguishing media appropriate for surrounding fire.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire. Reacts with water to form corrosive alkalis.

#### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Not considered flammable but may burn at high temperatures.

**Explosion Hazard:** Product is not explosive as supplied. However, when cured and dried this product may produce explosive combustible dust when cut, sanded, ground, or otherwise processed.

**Reactivity:** Hydrofluoric acid will react with and dissolve glass, and other silica containing material. May react exothermically with water releasing heat. Adding an acid to a base or base to an acid may cause violent reaction.

#### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

# MULTIMAX™ Lite

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Hazardous Combustion Products:** None known.

### Reference to Other Sections

Refer to Section 9 for flammability properties.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Do not breathe dust. Do not get in eyes, on skin, or on clothing. Avoid generating dust. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.

#### 6.1.1. For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protective equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

### 6.3. Methods and Materials for Containment and Cleaning Up

**For Containment:** Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions. Avoid generation of dust during clean-up of spills.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Vacuum clean-up is preferred. If sweeping is required use a dust suppressant. Avoid generation of dust during clean-up of spills. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

### 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Additional Hazards When Processed:** May release corrosive vapors. Accumulation and dispersion of dust with an ignition source can cause a combustible dust explosion. Keep dust levels to a minimum and follow applicable regulations.

**Precautions for Safe Handling:** Obtain special instructions before use. Do not breathe dust. Do not get in eyes, on skin, or on clothing. Do not handle until all safety precautions have been read and understood. Handle empty containers with care because they may still present a hazard. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations. Avoid creating or spreading dust. Proper grounding procedures to avoid static electricity should be followed.

**Storage Conditions:** Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Store in original container or corrosive resistant and/or lined container.

**Incompatible Materials:** Strong acids, strong bases, strong oxidizers. Fluorinated compounds. Ammonia. Ammonium salts. Aluminum.

### 7.3. Specific End Use(s)

Adhesive. For professional use only.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Cement, portland, chemicals (65997-15-1)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup> (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)

# MULTIMAX™ Lite

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

<b>USA ACGIH</b>	ACGIH chemical category	Not Classifiable as a Human Carcinogen
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable fraction)
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable dust)
<b>USA IDLH</b>	US IDLH (mg/m <sup>3</sup> )	5000 mg/m <sup>3</sup>
<b>Alberta</b>	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
<b>British Columbia</b>	OEL TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup> (particulate matter containing no Asbestos and <1% Crystalline silica-respirable particulate)
<b>Manitoba</b>	OEL TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup> (particulate matter containing no Asbestos and <1% Crystalline silica-respirable particulate matter)
<b>New Brunswick</b>	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (particulate matter containing no Asbestos and <1% Crystalline silica)
<b>Newfoundland &amp; Labrador</b>	OEL TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup> (particulate matter containing no Asbestos and <1% Crystalline silica-respirable particulate matter)
<b>Nova Scotia</b>	OEL TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup> (particulate matter containing no Asbestos and <1% Crystalline silica-respirable particulate matter)
<b>Nunavut</b>	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
<b>Ontario</b>	OEL TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline silica-respirable)
<b>Prince Edward Island</b>	OEL TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup> (particulate matter containing no Asbestos and <1% Crystalline silica-respirable particulate matter)
<b>Québec</b>	VEMP (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline silica-total dust) 5 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline silica-respirable dust)
<b>Saskatchewan</b>	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
<b>Saskatchewan</b>	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
<b>Yukon</b>	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
<b>Yukon</b>	OEL TWA (mg/m <sup>3</sup> )	30 mppcf 10 mg/m <sup>3</sup>
<b>Calcium oxide (1305-78-8)</b>		
<b>USA ACGIH</b>	ACGIH TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>USA IDLH</b>	US IDLH (mg/m <sup>3</sup> )	25 mg/m <sup>3</sup>
<b>Alberta</b>	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>British Columbia</b>	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>Manitoba</b>	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>Newfoundland &amp; Labrador</b>	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>Nova Scotia</b>	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL STEL (mg/m <sup>3</sup> )	4 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL STEL (mg/m <sup>3</sup> )	4 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>Ontario</b>	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>Prince Edward Island</b>	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>Québec</b>	VEMP (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>

# MULTIMAX™ Lite

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Saskatchewan	OEL STEL (mg/m <sup>3</sup> )	4 mg/m <sup>3</sup>
Saskatchewan	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
Yukon	OEL STEL (mg/m <sup>3</sup> )	4 mg/m <sup>3</sup>
Yukon	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>Quartz (14808-60-7)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable particulate matter)
USA ACGIH	ACGIH chemical category	A2 - Suspected Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	50 µg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup> (respirable dust)
USA IDLH	US IDLH (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup> (respirable dust)
Alberta	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable particulate)
British Columbia	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable)
Manitoba	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable particulate matter)
New Brunswick	OEL TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup> (respirable fraction)
Newfoundland & Labrador	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable particulate matter)
Nova Scotia	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable particulate matter)
Nunavut	OEL TWA (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup> (respirable fraction)
Northwest Territories	OEL TWA (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup> (respirable fraction)
Ontario	OEL TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup> (designated substances regulation-respirable)
Prince Edward Island	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable particulate matter)
Québec	VEMP (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup> (respirable dust)
Saskatchewan	OEL TWA (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup> (respirable fraction)
Yukon	OEL TWA (mg/m <sup>3</sup> )	300 particle/mL
<b>Limestone (1317-65-3)</b>		
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable dust)
Alberta	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
British Columbia	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup> (total dust)
British Columbia	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (total dust) 3 mg/m <sup>3</sup> (respirable fraction)
New Brunswick	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (particulate matter containing no Asbestos and <1% Crystalline silica)
Nunavut	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
Nunavut	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Northwest Territories	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
Northwest Territories	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Québec	VEMP (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Limestone, containing no Asbestos and <1% Crystalline silica-total dust)
Saskatchewan	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
Saskatchewan	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Yukon	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
Yukon	OEL TWA (mg/m <sup>3</sup> )	30 mppcf 10 mg/m <sup>3</sup>
<b>Magnesium oxide (MgO) (1309-48-4)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable particulate matter)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (fume, total particulate)
USA IDLH	US IDLH (mg/m <sup>3</sup> )	750 mg/m <sup>3</sup> (fume)
Alberta	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (fume)
British Columbia	OEL STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (respirable dust and fume)

# MULTIMAX™ Lite

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

<b>British Columbia</b>	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (fume, inhalable) 3 mg/m <sup>3</sup> (respirable dust and fume)
<b>Manitoba</b>	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable particulate matter)
<b>New Brunswick</b>	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (fume)
<b>Newfoundland &amp; Labrador</b>	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable particulate matter)
<b>Nova Scotia</b>	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable particulate matter)
<b>Nunavut</b>	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup> (inhalable fraction)
<b>Nunavut</b>	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable fraction)
<b>Northwest Territories</b>	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup> (inhalable fraction)
<b>Northwest Territories</b>	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable fraction)
<b>Ontario</b>	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable)
<b>Prince Edward Island</b>	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable particulate matter)
<b>Québec</b>	VEMP (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (fume)
<b>Saskatchewan</b>	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup> (inhalable fraction)
<b>Saskatchewan</b>	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable fraction)
<b>Yukon</b>	OEL STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (fume)
<b>Yukon</b>	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (fume)
<b>Chromium, ion (Cr6+) (18540-29-9)</b>		
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	5 µg/m <sup>3</sup>
<b>Calcium Sulfate Hemihydrate (13397-24-5)</b>		
<b>USA ACGIH</b>	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable particulate matter)
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable fraction)
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable dust)
<b>Alberta</b>	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
<b>British Columbia</b>	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup> (total dust)
<b>British Columbia</b>	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (total dust) 3 mg/m <sup>3</sup> (respirable fraction)
<b>Manitoba</b>	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable particulate matter)
<b>Newfoundland &amp; Labrador</b>	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable particulate matter)
<b>Nova Scotia</b>	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable particulate matter)
<b>Ontario</b>	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable)
<b>Prince Edward Island</b>	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable particulate matter)
<b>Québec</b>	VEMP (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline silica-total dust) 5 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline silica-respirable dust)
<b>Saskatchewan</b>	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
<b>Saskatchewan</b>	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
<b>Yukon</b>	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
<b>Yukon</b>	OEL TWA (mg/m <sup>3</sup> )	30 mppcf 10 mg/m <sup>3</sup>
<b>Perlite (93763-70-3)</b>		
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (General Industry - total dust)
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable dust)
<b>British Columbia</b>	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (total dust) 3 mg/m <sup>3</sup> (respirable fraction)
<b>New Brunswick</b>	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (particulate matter containing no Asbestos and <1% Crystalline silica)
<b>Nunavut</b>	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>

# MULTIMAX™ Lite

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Nunavut	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Northwest Territories	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
Northwest Territories	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Saskatchewan	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
Saskatchewan	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Yukon	OEL TWA (mg/m <sup>3</sup> )	30 mppcf
<b>Silica, crystalline (general form) (Not Applicable)</b>		
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	50 µg/m <sup>3</sup> (excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays)

### 8.2. Exposure Controls

**Appropriate Engineering Controls:** Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Proper grounding procedures to avoid static electricity should be followed.

**Personal Protective Equipment:** Gloves. Protective clothing. Protective goggles. Face shield. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics. Corrosion-proof clothing.

**Hand Protection:** Wear protective gloves.

**Eye and Face Protection:** Chemical safety goggles and face shield.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

**Other Information:** When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

Physical State	: Solid
Appearance	: Not available
Odor	: Not available
Odor Threshold	: Not available
pH	: Not available
Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: Not available
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20°C	: Not available
Relative Density	: Not available
Specific Gravity	: Not available
Solubility	: Not available
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not available

# MULTIMAX™ Lite

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Hydrofluoric acid will react with and dissolve glass, and other silica containing material. May react exothermically with water releasing heat. Adding an acid to a base or base to an acid may cause violent reaction.
- 10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials. Sparks, heat, open flame and other sources of ignition. Dust accumulation.
- 10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers. Fluorinated compounds. Ammonia. Ammonium salts. Aluminum.
- 10.6. Hazardous Decomposition Products:** Metal oxides. Sulfur oxides. Carbon oxides (CO, CO<sub>2</sub>).

### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1. Information on Toxicological Effects - Product

**Acute Toxicity (Oral):** Not classified

**Acute Toxicity (Dermal):** Not classified

**Acute Toxicity (Inhalation):** Not classified

**LD50 and LC50 Data:** Not available

**Skin Corrosion/Irritation:** Causes severe skin burns and eye damage.

**Eye Damage/Irritation:** Causes serious eye damage.

**Respiratory or Skin Sensitization:** May cause an allergic skin reaction.

**Germ Cell Mutagenicity:** Not classified

**Carcinogenicity:** May cause cancer (Inhalation).

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** May cause respiratory irritation.

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** May be corrosive to the respiratory tract. Accelerated Silicosis can occur with exposure to high concentrations of respirable crystalline silica over a relatively short period; lung lesions can appear within five years of the initial exposure. The progression can be rapid. Accelerated silicosis is similar to chronic or ordinary silicosis, except that lung lesions appear earlier and the progression is more rapid.

Acute Silicosis can occur with exposures to very high concentrations of respirable crystalline silica over a very short time period, sometimes as short as a few months. The symptoms of acute silicosis include progressive shortness of breath, fever, cough and weight loss. Acute silicosis can be fatal.

**Symptoms/Injuries After Skin Contact:** May cause an allergic skin reaction. Redness, pain, swelling, itching, burning, dryness, and dermatitis. Concrete may cause dry skin, discomfort, irritation, severe burns, and dermatitis. Unhardened concrete is capable of causing dermatitis by irritation and allergy. Concrete dust, in association with sweat and friction, can lead to skin irritation and dermatitis. Skin affected by dermatitis may include symptoms such as, redness, itching, rash, scaling, and cracking. Allergic contact dermatitis is caused by sensitization to hexavalent chromium (chromate) present in concrete. The reaction can range from a mild rash to severe skin ulcers.

**Symptoms/Injuries After Eye Contact:** Causes permanent damage to the cornea, iris, or conjunctiva. Concrete may cause immediate or delayed irritation or inflammation. Eye contact with wet concrete can cause moderate eye irritation, chemical burns and blindness. Eye exposures require immediate first aid and medical attention to prevent significant damage to the eye.

**Symptoms/Injuries After Ingestion:** May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

**Chronic Symptoms:** Causes damage to organs through prolonged or repeated exposure. May cause cancer. Repeated exposure to respirable (airborne) crystalline silica dust will cause lung damage in the form of silicosis. Some studies show that exposure to respirable crystalline silica (without silicosis) or that the disease silicosis may be associated with the increased incidence of several autoimmune disorders such as scleroderma (thickening of the skin), systemic lupus erythematosus, rheumatoid arthritis and diseases affecting the kidneys. Silicosis increases the risk of tuberculosis. Some studies show an increased incidence of chronic kidney disease and end-stage renal disease in workers exposed to respirable crystalline silica.

#### 11.2. Information on Toxicological Effects - Ingredient(s)

**LD50 and LC50 Data:**

Calcium oxide (1305-78-8)	
LD50 Oral Rat	> 2000 mg/kg
LD50 Dermal Rabbit	> 2500 mg/kg

# MULTIMAX™ Lite

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

<b>Quartz (14808-60-7)</b>	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rat	> 5000 mg/kg
<b>Magnesium oxide (MgO) (1309-48-4)</b>	
LD50 Oral Rat	3870 mg/kg
<b>Perlite (93763-70-3)</b>	
LD50 Oral Rat	12960 mg/kg (Mouse)
<b>Quartz (14808-60-7)</b>	
IARC Group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
<b>Chromium, ion (Cr6+) (18540-29-9)</b>	
IARC Group	1
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
OSHA Specifically Regulated Carcinogen List	In OSHA Specifically Regulated Carcinogen list.
<b>Sepiolite (Mg2H2(SiO3)3.xH2O) (63800-37-3)</b>	
IARC Group	3
<b>Silica, crystalline (general form) (Not Applicable)</b>	
IARC Group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
OSHA Specifically Regulated Carcinogen List	In OSHA Specifically Regulated Carcinogen list.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

Ecology - General: Harmful to aquatic life.

<b>Calcium oxide (1305-78-8)</b>	
LC50 Fish 1	50.6 mg/l
<b>Chromium, ion (Cr6+) (18540-29-9)</b>	
LC50 Fish 1	36.2 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
LC50 Fish 2	7.6 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)

### 12.2. Persistence and Degradability

<b>MULTIMAX™ Lite</b>	
Persistence and Degradability	Not established.

### 12.3. Bioaccumulative Potential

<b>MULTIMAX™ Lite</b>	
Bioaccumulative Potential	Not established.
<b>Calcium oxide (1305-78-8)</b>	
BCF Fish 1	(no bioaccumulation)

12.4. Mobility in Soil Not available

### 12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

**Ecology - Waste Materials:** Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

## SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

# MULTIMAX™ Lite

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

- 14.1. In Accordance with DOT** Not regulated for transport  
**14.2. In Accordance with IMDG** Not regulated for transport  
**14.3. In Accordance with IATA** Not regulated for transport  
**14.4. In Accordance with TDG** Not regulated for transport

## SECTION 15: REGULATORY INFORMATION

### 15.1. US Federal Regulations

<b>MULTIMAX™ Lite</b>	
<b>SARA Section 311/312 Hazard Classes</b>	Health hazard - Specific target organ toxicity (single or repeated exposure) Health hazard - Carcinogenicity Health hazard - Respiratory or skin sensitization Health hazard - Serious eye damage or eye irritation Health hazard - Skin corrosion or Irritation
<b>Cement, portland, chemicals (65997-15-1)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Calcium oxide (1305-78-8)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Quartz (14808-60-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Limestone (1317-65-3)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Magnesium oxide (MgO) (1309-48-4)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

### 15.2. US State Regulations

<b>Quartz (14808-60-7)</b>	
<b>U.S. - California - Proposition 65 - Carcinogens List</b>	WARNING: This product contains chemicals known to the State of California to cause cancer.
<b>Chromium, ion (Cr6+) (18540-29-9)</b>	
<b>U.S. - California - Proposition 65 - Carcinogens List</b>	WARNING: This product contains chemicals known to the State of California to cause cancer.
<b>U.S. - California - Proposition 65 - Developmental Toxicity</b>	WARNING: This product contains chemicals known to the State of California to cause birth defects.
<b>Silica, crystalline (general form)</b>	
<b>U.S. - California - Proposition 65 - Carcinogens List</b>	WARNING: This product contains chemicals known to the State of California to cause cancer.
<b>Cement, portland, chemicals (65997-15-1)</b>	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Calcium oxide (1305-78-8)</b>	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Quartz (14808-60-7)</b>	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Limestone (1317-65-3)</b>	

# MULTIMAX™ Lite

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

U.S. - Massachusetts - Right To Know List  
 U.S. - New Jersey - Right to Know Hazardous Substance List  
 U.S. - Pennsylvania - RTK (Right to Know) List

### Magnesium oxide (MgO) (1309-48-4)

U.S. - Massachusetts - Right To Know List  
 U.S. - New Jersey - Right to Know Hazardous Substance List  
 U.S. - Pennsylvania - RTK (Right to Know) List

### Chromium, ion (Cr6+) (18540-29-9)

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  
 U.S. - Pennsylvania - RTK (Right to Know) List

### Calcium Sulfate Hemihydrate (13397-24-5)

U.S. - New Jersey - Right to Know Hazardous Substance List  
 U.S. - Pennsylvania - RTK (Right to Know) List

### Perlite (93763-70-3)

U.S. - Massachusetts - Right To Know List  
 U.S. - New Jersey - Right to Know Hazardous Substance List  
 U.S. - Pennsylvania - RTK (Right to Know) List

## 15.3. Canadian Regulations

### Cement, portland, chemicals (65997-15-1)

Listed on the Canadian DSL (Domestic Substances List)

### Calcium oxide (1305-78-8)

Listed on the Canadian DSL (Domestic Substances List)

### Quartz (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List)

### Limestone (1317-65-3)

Listed on the Canadian NDSL (Non-Domestic Substances List)

### Magnesium oxide (MgO) (1309-48-4)

Listed on the Canadian DSL (Domestic Substances List)

### Calcium Sulfate Hemihydrate (13397-24-5)

Listed on the Canadian DSL (Domestic Substances List)

### Perlite (93763-70-3)

Listed on the Canadian DSL (Domestic Substances List)

### Water (7732-18-5)

Listed on the Canadian DSL (Domestic Substances List)

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Date of Preparation or Latest Revision** : 10/01/2019

**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

### GHS Full Text Phrases:

Acute Tox. 3 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 3
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Carc. 1	Carcinogenicity, Category 1
Carc. 1A	Carcinogenicity Category 1A
Carc. 1B	Carcinogenicity Category 1B
Comb. Dust	Combustible Dust
Eye Dam. 1	Serious eye damage/eye irritation Category 1

# MULTIMAX™ Lite

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Skin Corr. 1C	Skin corrosion/irritation Category 1C
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization, Category 1
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H331	Toxic if inhaled
H335	May cause respiratory irritation
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

NA GHS SDS 2015 (Can, US)