

1317-65-3

Limestone

<40%

Conforms to OSHA HazCom 2012 & CPR Standards

SAFETY DATA SHEET

PRO PATCH Product: **Revision Date:** 2017-08-16 Section 1. Product and Company Identification Product Name: PRO PATCH Recommended Use(s): Cementitious Patching compound Non-Recommended Use(s): Not specified Manufacturer: Proma Adhesives, 9801 Boulevard parkway, Aniou, OC, H1J 1P3, Canada Email: info@proma.ca Url: www.proma.ca Emergency Spills (CANUTEC): (613)996-6666 /Emergency contact number in Canada/U.S.A Emergency Contact: Section 2. Hazard Identification **GHS Classification for mixture:** Specific target organ toxicity - repeated exposure - Category 2 Specific target organ toxicity - single exposure - Category 3 (Respiratory) Carcinogenicity - Category 1A Serious eye damage/eye irritation - Category 1 Skin corrosion/irritation - Category 1 Skin sensitization - Category 1 **Pictograms:** Signal Words: Dange Hazard Statements: Causes severe skin burns and eye damage. Causes serious eye damage. May cause respiratory irritation. May cause cancer. Route of esposure: respiration. May cause damage to organs through prolonged or repeated exposure. Route of exposure: Respiration Affected organ: Lungs Precautionary Statements: General Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Wash hands thoroughly after handling. Wear protective gloves, Prevention eye protection and a dust mask. Response If exposed or concerned: Get medical advice/attention. Get medical advice if you feel unwell. IF IN EYES: Remove contact lenses, if present and easy to do, rinse with water for several minutes . IF ON SKIN: Rinse with water for several minutes. IF INHALED, Move the person to fresh air. IF INGESTED, call a poison center. Storage Store locked up. Disposal Dispose of contents/container in accordance with local regulations. Section 3. Composition / Information on Ingredients Identifiers Ingredients Percentage 14808-60-7 Crystalline silica Portland Cement <1 5% 65997-15-1 <30% 65997-16-2 Calcium Aluminate Cement <30%



SAFETY DATA SHEET

Section 4. First-Aid Measures

First-Aid: Eyes

IF IN EYES: Wash eyes with plenty of water. Hold eyelids open to ensure adequate flushing. Remove contact lenses if present and easy to do so. Continue rinsing. Seek medical attention if irritation or redness develops.

First-Aid: Skin

IF ON SKIN: Rince with water for several minutes. Take off all contaminated clothing and wash it before reuse. If redness or other symptoms occurs, seek medical advice/attention.

First-Aid: Ingestion

IF INGESTED: Call a poison center. Do not induce vomiting.

First-Aid: Inhalation

IF INHALED: Move the person to fresh air and keep at rest in a position comfortable for breathing. Seek medical attention if symptoms occur.

Section 5. Fire-Fighting Measures

Flammability

The product is not flammable by WHMIS/OSHA criteria.

Suitable Extinguishing Media

Use dry chemical, water spray, carbon dioxide or alcohol-resistant foam.

Unsuitable Extinguishing Media

Not available

Specific Hazards Arising from Combustion of Products

Combustion Products: May include and are not limited to Oxides of carbon (COx). **Heat & Fire:** The product is not flammable or combustible. Fire and heat may decompose the product and generate hazardous gas, vapor or dust.

Protective Measures for Fire-Fighting

Wear protective clothing to prevent contact with skin and eyes completely. Wear self-contained breathing apparatus for firefighting. Avoid direct contact with the substance. Avoid breathing gas, vapor or dust. In the case of large fires, evacuate residents who are downwind of fire.

Specific Hazards Arising from Combustion of Products

Explosion data:

Sensitivity to mechanical impact: Sensitivity to Static discharge: Not available Not available



SAFETY DATA SHEET

Section 6. Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures

Wear protective gloves, clothing and protective goggles to prevent contact with skin and eyes.

Avoid direct contact.

Avoid generating dust. See protective measures in section 7 & 8.

Environmental Precautions

Prevent entry into sewers, water courses, basements or confined areas. Dispose the material in accordance with the government regulation. If the product has entered a water course or sewer or contaminated soil or vegetation, advise the local emergency services and environmental authorities.

Clean-up Procedures

Collect and transfer to a closable container without splash or generating dust / mist. Dispose the material in accordance with the government regulations.

Section 7. Handling and Storage

Precautions for Safe Handling

Handling: Avoid direct contact with the substance. Avoid breathing dust. Keep container tightly closed. Wear protective gloves, clothing and protective goggles to prevent contact with skin and eyes. Ensure there is sufficient ventilation of the area. Do not eat or drink during handling. Report immediately if physical damage, leakage or spillage occurs.

General hygiene advice: Launder contaminated clothing before reuse. Wash any exposed area of body thoroughly after handling before eating, drinking or smoking.

Conditions for Safe Storage

Respiratory Protection:

Store locked up. Keep container tightly closed. Store in a well-ventilated area. Keep out of the reach of children. Respect the laws of the safety standards and occupational health.

Section 8. Exposure Controls / Personal Protection					
Control Parameters / E	xposure Guideline				
	Occupational Exposure Limits	5			
Ingredients	OSHA-PEL	ACGIH-TLV			
Crystalline silica	(10 mg/m ³)/(%SiO ₂ +2) (resp)	0,05 mg/m³ (resp)			
	(30 mg/m ³)/(%SiO ₂ +2) (total)				
Portland Cement	5 mg/m ³ (resp), 15 mg/m ³ (total)	1 mg/m ³			
Calcium Aluminate Cement	5 mg/m ³ (resp), 15 mg/m ³ (total)	5 mg/m ³ (resp), 10 mg/m ³ (total)			
Limestone	5 mg/m ³ (resp), 15 mg/m ³ (total)	10 mg/m³ (total)			
Control Parameters / E	xposure Controls				
Engineering Controls: Use v fume, vapor etc.)	entilation adequate to keep exposures	below recommended exposure limits. (airborne levels of dust,			
Control Parameters / I	ndividual Protective Measures	i			
Eye/Face Protection:	Wear Safety goggle	Wear Safety goggles. Don't use eye lens.			
Skin and Body Protection	Wear protective clo	Wear protective clothing. Wear a dust mask.			
Hand Protection:	Wear impermeable	Wear impermeable gloves.			

If ventilation is inadequate or in the case of mechanical work on

cured material or when mixing use an adequate respiratory equipment.



SAFETY DATA SHEET

Section 9. Physical and Chemical Properties						
Basic physical and chemic	al properties Information	ation				
Physical state:	Powder					
Color:	Grey					
Odour:	Odorless					
Odour threshold:	Not available					
pH (in water):	11 to 12					
Melting/freezing point:	Not available					
Boiling point:	Not available					
Flash point:	Non flammable					
Evaporation rate:	Not available					
Flammability:	Non flammable					
Upper Explosive Limit:	Not available					
Lower Explosive Limit:	Not available					
Vapor pressure:	Not available					
Vapor density:	Not available					
Specific gravity (kg/L):	1,1					
Solubility uncured:	Slightly soluble					
Solubility cured:	Not available					
Octanol/Water coefficient:	Not available					
Auto-ignition temperature:	Not available					
Decomposition temperature:	Not available					
Viscosity (kcPs @ 21°C):	Not available					
Oxidizing Properties:	Not available					
Explosive Properties:	Not available					
VOC content (g/l)	0					
Section 10. Chemical St	ability & Reactivity	/ Information				
Stability/Reactivity		Stable under ambient condition.				
Possibility of Hazardous R	eactions	None				
Conditions to Avoid		Incompatible materials.				
Materials to Avoid		Strong organic acids.				
Hazardous Products of De	composition	May include and are not limited to Oxides of carbon.				
Section 11. Toxicologic	al Information					
Toxicological Information						
•		posure cause damage to lungs and kidneys.				
Ingestion: The product is not class		,				
Toxicological Data: No toxicologi	-					
Carcinogenicity: This product is o	classified as carcinogen 1A	because of the existence of crystalline silice above the				
thresholds of occupational health.	-	-				
Inhalation: May cause respiratory	riritation.					
Toxicological Information	for Component					
-	Limostono	Ouartz (SiO2)				

Toxicity - Oral Toxicity - Dermal Toxicity - Inhalation Limestone LD50 Rat 6450 mg/kg LD50 Rabbit > 2000 mg/kg LC50 (4h) Rat > 5 mg/L Quartz (SiO2) LD50 Rat 22,5 g/kg LD50 Rabbit > 2000 mg/kg LC50 (4h) Rat > 20 mg/L



SAFETY DATA SHEET

Section 12. Ecologic	cal Information			
Ecotoxicity:	No ecotoxicity values for this product. Avoid release into the environment.			
Persistence and Degrada				
Bioaccumulative Potentia				
Mobility in Soil: Other Adverse Effects:	Not available Not available			
Other Adverse Effects:				
Section 13. Disposa				
Waste Disposal Regul				
Avoid release to the environment. Users need to pay attention to the possible existence of regional or national regulations regarding disposal.				
	rtation Information [ADR-UN, DOT, ICAO, IMDG, TDGR]			
UN Number:	NOT CLASSIFIED AS DANGEROUS GOODS			
UN Proper Shipping Name				
Hazard Class:				
Packing group:				
Section 15. Regulate	ory Information			
	rironmental Regulations for Product			
No regulation data for produc	-			
Safety, Health and Env	vironmental Regulations for Component			
Limestone				
	WHMIS Classification: Class D Division 2 Subdivision A - Very toxic material causing other toxic			
6	effects. DSL / NDSL: Listed on non-domestic substance list (NDSL).			
States:	Hazardous Substance Right to know list (RTK): Massachusetts. New Jersey. Pennsylvania.			
i de la constante de	Foxic Substances Control Act (TSCA): listed on TSCA inventory			
Quartz (SiO2)				
	WHMIS Classification: Class D Division 2 Subdivision A - Very toxic material causing other toxic			
	effects. DSL / NDSL: Listed on the Canadian DSL (Domestic Substance List) inventory.			
	isted on the Canadian Ingredient Disclosure List.			
States:	Hazardous Substance Right to know list (RTK): Massachusetts. New Jersey. Pennsylvania.			
	California-Proposition 65 Carcinogens List: Crystalline silica is know to the State of			
(California to cause cancer.			
Section 16. Other In	formation			
Date of preparatio				
Version :	n: August 16 2017 1.1			
Prepared by :	PROMA ADHESIVES INC			
Other Information	Disclaimer:			
	lieved to be correct but does not purport to be all inclusive and shall be used only as a guide. This able for any damage resulting from handling or from contact with the above product.			
Glossary				
ACGIH:	American Conference of Governmental Industrial Hygienists.			
	European Road Transport.			
	Chemical Abstracts Service.			
	JS Department of Transportation USA.			
	Canadian Domestic Substances List. JS Environmental Protection Agency.			
	International Civil Aviation Organization.			
	international Maritime Dangerous Goods Code.			
	ethal concentration that will kill 50 percent of the test animals within a specified time.			
LD50:	The dose required to produce the death in 50 percent of the exposed species within a			
S	specified time.			



SAFETY DATA SHEET

N/Ap:	Not applicable.	
N/Av:	Not available.	
N/D:	Not determined.	
NDSL:	Canadian Non-Domestic Substances List.	
NIOSH:	National Institute for Occupational Safety and Health.	
OSHA:	Occupational Safety and Health Administration, US Department of Labor.	
REL:	A recommended exposure limit (REL) is an occupational exposure limit that has been	
	recommended by the United States National Institute for Occupational Safety and Health to	
	the Occupational Safety and Health Administration (OSHA) for adoption as a permissible	
	exposure limit.	
RTECS:	Registry of Toxic Effects of Chemical Substances.	
SARA:	Superfund Amendments and Reauthorization Act.	
STEL:	A short-term exposure limit (STEL) is the acceptable average exposure over a short period	
	of time, usually 15 minutes as long as the time-weighted average is not exceeded.	
TDGR:	Transportation of Dangerous Goods Regulations.	
TLV:	The threshold limit value of a chemical substance is a level to which it is believed a worker	
	can be exposed day after day for a working lifetime without adverse health effects. Strictly	
	speaking, TLV is a reserved term of the American Conference of Governmental Industrial	
	Hygienists (ACGIH). However, it is sometimes loosely used to refer to other similar	
	concepts used in occupational health and toxicology. TLVs, along with biological exposure	
	indices (BEIs), are published annually by the ACGIH.	
TSCA:	Toxic Substances Control Act.	
TWA:	A time-weighted average is used to calculate a workers daily exposure to a hazardous	
	substance (such as chemicals, dusts, fumes, mists, gases, or vapors) or agent (such as	
	occupational noise), averaged to an 8-hour workday, taking into account the average levels	
	of the substance or agent and the time spent in the area. This is the guideline OSHA uses to	
	determine permissible exposure limits (PELs) and is essential in assessing a worker's	
	exposure and determining what protective measures should be taken.	
UN:	United Nations.	